

## Dati tecnici

### Private Line

### Commercial Line

### Industrial Line

#### Vulcan 1000



#### Vulcan 5000



#### Vulcan S25



#### Vulcan S100



#### Vulcan S250



#### Vulcan S500



|                     |                  |                |                      |                       |                       |                       |
|---------------------|------------------|----------------|----------------------|-----------------------|-----------------------|-----------------------|
| Capacità            | 1000 l/h         | 5000 l/h       | 25 m <sup>3</sup> /h | 100 m <sup>3</sup> /h | 250 m <sup>3</sup> /h | 500 m <sup>3</sup> /h |
| Misura massima tubo | 25 mm (1")       | 50 mm (2")     | 100 mm (4")          | 150 mm (6")           | 250 mm (10")          | 500 mm (20")          |
| Tensione (V)        | 24 Volt          | 24 Volt        | 24 Volt              | 24 Volt               | 24 Volt               | 24 Volt               |
| Consumo corrente    | 1,75 Watt        | 2,0 Watt       | 2,25 watt            | 2,5 Watt              | 2,75 Watt             | 3,25 Watt             |
| Cavo ad impulsi     | 2 x 0,5 m piatto | 2 x 1 m piatto | 4 x 2 m piatto       | 6 x 4 m piatto        | 8 x 10 m piatto       | 10 x 30 m piatto      |
| Dimensioni (mm)     | 60/90/30         | 85/150/30      | 125/200/35           | 160/200/40            | 205/295/45            | 225/325/45            |
| Campo di frequenza  | 3-32 KHz         | 3-32 KHz       | 3-32 KHz             | 3-32 KHz              | 3-32 KHz              | 3-32 KHz              |
| Dimensioni          | 200 mm           | 350 mm         | 600 mm               | 1200 mm               | 2500 mm               | 5000 mm               |
| Programmi           | -                | -              | 5                    | 10                    | 10                    | 10                    |

### Assorbimento nominale

|     |                         |                         |                         |                         |                         |                         |
|-----|-------------------------|-------------------------|-------------------------|-------------------------|-------------------------|-------------------------|
| In  | 87-260 Volt<br>50-60 Hz | 87-260 Volt<br>50-60 Hz | 87-260 Volt<br>50-60 Hz | 87-260 Volt<br>50-60 Hz | 87-260 Volt<br>50-60 Hz | 87-260 Volt<br>50-60 Hz |
| Out | 24 Volt<br>600 mA       | 24 Volt<br>600 mA       | 24 Volt<br>600 mA       | 24 Volt<br>600 mA       | 24 Volt<br>600 mA       | 24 Volt<br>600 mA       |